

provision-platan-gateway-GW24

#Platan Gateway configuration version:0.00.02

Global Settings

Network Settings

#####Processor#####

#Configure the static IP address, submask, gateway and DNS server

#Requires a reboot

#Configure the WAN port type; 0-DHCP, 2-Static IP Address(default))

network.internet_port.type = 0

network.internet_port.ip = 192.168.1.250

network.internet_port.mask = 255.255.255.0

network.internet_port.gateway = 192.168.1.1

network.internet_port.dns = 8.8.8.8

network.internet_port.mac =

#####VoIP Card#####

#Configure the static IP address, submask, gateway and DNS server

#Requires a reboot

#Configure the WAN port type; 0-DHCP, 2-Static IP Address(default)

network.voip_port.type = 0

network.voip_port.ip = 192.168.1.250

network.voip_port.mask = 255.255.255.0

network.voip_port.gateway = 192.168.1.1

network.voip_port.dns= 8.8.8.8

#Set the HTTP port (80 by default)

#Wymaga restartu

network.port.http = 80

Other settings

#Set the auto provisioning mode (0-Disabled (default), 1-Power on/Repeatedly,

auto_provision.mode = 0

auto_provision.server.url =

auto_provision.server.username =

auto_provision.server.password =

#Set the new password (44444444) for the administrator

security.user_password.old = 44444444

security.user_password.new = 44444444

#Remote access (0-Disabled (default), 1-Enabled), (remote_access.access_myipbx) - dostęp dla serwisu mojacentrala.pl

remote_access.access_myipbx = 0

remote_access.service_enable = 0

provision-platan-gateway-GW24

#Date & time

#Synchronise with computer(0-Manual (default), 1-NTP)

local_time.manual_time_enable = 0

#NTP Server URL (default null)

local_time.ntp_server =

#Daylight Saving Time (0-Disabled, 1-Automatic (Default))

local_time.summer_time = 1

#Time zone (-12 to +12, The default vaule is +1)

local_time.time_zone = +1

Common Settings

#Allow switching the RTP stream (0-Disabled,1-Enabled (default))

common.switch_rtp_stream = 1

#Timeout period if no RTP packets are received

#Value: 15,30,45,60,75 (default),120,180,240,300,360[s]

common.rtp_packets_timeout = 75

#####Codecs#####

#Codec: 0-None, 1-G.711a, 2-G.711u, 3-GSM, 4-G.726, 5-G.729a.

common.codec.1 = 1

common.codec.2 = 2

common.codec.3 = 3

common.codec.4 = 4

common.codec.5 = 0

#####Remote attacks#####

#Blocking time - Time for which an IP address that originates inquiries will be blocked.

#The time may vary from 0 (attack blocking #disabled) to 60 minutes. Default - 15

common.blocking_time = 15

#Time-interval for attacks counting (events of a given type), after which the IP address will be blacklisted.

#The time may vary from 1 to 30 minutes. Default - 5

common.attacks_counting_interval = 5

##Threshlod number of events to detect threats

#Set the threshold number of frames with syntax error.

#The value may vary from 0 (attack blocking disabled) to 1000. Default - 300

common.threats.syntax_error = 300

#Set the threshold number of authentications to nonexistent accounts.

#The value may vary from 0 (attack blocking disabled) to 1000. Default - 300

common.threats.user_errors = 300

#Set the threshold number of authentication errors (wrong passwords) to existing accounts.

provision-platan-gateway-GW24

#The value may vary from 0 (attack blocking disabled) to 1000. Default - 300
common.threats.authentication_errors = 300

Individual settings

Line1 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.1.enable = 0

#Configure the ID
account.1.id =

#Configure the SIP server address (domain) and port
account.1.sip_server_host =

#Configure the register user name
account.1.user_name =

#Configure the register password
account.1.password =

#Configure Dial number (#000 to #999)
account.1.extension_number = #201

#Configure the display name of account
account.1.display_name =

#Configure the SIP server proxy
account.1.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.1.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.1.call_recording_announcement = 0

Advanced settings

#Domain
account.1.domain =

#Configure the sip server expires (Timeout 60 by default)
account.1.sip_server_expires = 60

provision-platan-gateway-GW24

#Źródło CLIP, 0-User name (Default), 1-Display name

account.1.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.1.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.1.dtmf.out_RFC2833 = 1

account.1.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.1.dtmf.in_DTMF = 1

account.1.dtmf.in_RFC2833 = 1

account.1.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.1.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.1.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.1.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.1.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.1.media_type_change = 0

#Configure the MSN_DDI of account

account.1.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.1.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.1.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.1.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.1.intl_clip.incoming.2 =

#Presented prefix 2.

account.1.intl_clip.presented.2 =

provision-platan-gateway-GW24

```
#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)
account.1.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)
```

```
##### Line2 settings
```

```
#####
```

```
##### Basic settings #####
```

```
#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.2.enable = 0
```

```
#Configure the ID
```

```
account.2.id =
```

```
#Configure the SIP server address (domain) and port
```

```
account.2.sip_server_host =
```

```
#Configure the register user name
```

```
account.2.user_name =
```

```
#Configure the register password
```

```
account.2.password =
```

```
#Configure Dial number (#000 to #999)
```

```
account.2.extension_number = #202
```

```
#Configure the display name of account
```

```
account.2.display_name =
```

```
#Configure the SIP server proxy
```

```
account.2.outbound_proxy_enable =
```

```
#Call recording (0-Disabled (Default), 1-Enabled)
```

```
account.2.call_recording_enable = 0
```

```
#Announcement (0-None (Default), 1 to 4 )
```

```
account.2.call_recording_announcement = 0
```

```
##### Advanced setting s#####
```

```
#Domain
```

```
account.2.domain =
```

```
#Configure the sip server expires (Timeout 60 by default)
```

```
account.2.sip_server_expires = 60
```

provision-platan-gateway-GW24

#Źródło CLIP, 0-User name (Default), 1-Display name
account.2.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.2.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled
account.2.dtmf.out_RFC2833 = 1
account.2.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)
account.2.dtmf.in_DTMF = 1
account.2.dtmf.in_RFC2833 = 1
account.2.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))
account.2.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))
account.2.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)
account.2.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))
account.2.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)
account.2.media_type_change = 0

#Configure the MSN_DDI of account
account.2.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)
account.2.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))
account.2.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).
#Presented prefix 1 ("00" - Default)
account.2.intl_clip.presented.1 = 00

#Incoming prefix 2.
account.2.intl_clip.incoming.2 =

#Presented prefix 2.
account.2.intl_clip.presented.2 =

provision-platan-gateway-GW24

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)
account.2.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line3 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.3.enable = 0

#Configure the ID
account.3.id =

#Configure the SIP server address (domain) and port
account.3.sip_server_host =

#Configure the register user name
account.3.user_name =

#Configure the register password
account.3.password =

#Configure Dial number (#000 to #999)
account.3.extension_number = #203

#Configure the display name of account
account.3.display_name =

#Configure the SIP server proxy
account.3.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.3.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.3.call_recording_announcement = 0

#####Advanced settings#####

#Domain
account.3.domain =

#Configure the sip server expires (Timeout 60 by default)
account.3.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

provision-platan-gateway-GW24

account.3.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.3.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.3.dtmf.out_RFC2833 = 1

account.3.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.3.dtmf.in_DTMF = 1

account.3.dtmf.in_RFC2833 = 1

account.3.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.3.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.3.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.3.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.3.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.3.media_type_change = 0

#Configure the MSN_DDI of account

account.3.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.3.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.3.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.3.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.3.intl_clip.incoming.2 =

#Presented prefix 2.

account.3.intl_clip.presented.2 =

#Dialplan rule (112|9|[89]x|11|[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

provision-platan-gateway-GW24

account.3.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line4 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.4.enable = 0

#Configure the ID
account.4.id =

#Configure the SIP server address (domain) and port
account.4.sip_server_host =

#Configure the register user name
account.4.user_name =

#Configure the register password
account.4.password =

#Configure Dial number (#000 to #999)
account.4.extension_number = #204

#Configure the display name of account
account.4.display_name =

#Configure the SIP server proxy
account.4.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.4.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.4.call_recording_announcement = 0

Advanced settings

#Domain
account.4.domain =

#Configure the sip server expires (Timeout 60 by default)
account.4.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.4.source_clip = 0

provision-platan-gateway-GW24

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.4.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.4.dtmf.out_RFC2833 = 1

account.4.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.4.dtmf.in_DTMF = 1

account.4.dtmf.in_RFC2833 = 1

account.4.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.4.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.4.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.4.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.4.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.4.media_type_change = 0

#Configure the MSN_DDI of account

account.4.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.4.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.4.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.4.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.4.intl_clip.incoming.2 =

#Presented prefix 2.

account.4.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.4.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

provision-platan-gateway-GW24

```
##### Line5 settings
#####

##### Basic settings #####

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.5.enable = 0

#Configure the ID
account.5.id =

#Configure the SIP server address (domain) and port
account.5.sip_server_host =

#Configure the register user name
account.5.user_name =

#Configure the register password
account.5.password =

#Configure Dial number (#000 to #999)
account.5.extension_number = #205

#Configure the display name of account
account.5.display_name =

#Configure the SIP server proxy
account.5.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.5.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4 )
account.5.call_recording_announcement = 0

##### Advanced settings #####

#Domain
account.5.domain =

#Configure the sip server expires (Timeout 60 by default)
account.5.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.5.source_clip = 0
```

provision-platan-gateway-GW24

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.5.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled
account.5.dtmf.out_RFC2833 = 1
account.5.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)
account.5.dtmf.in_DTMF = 1
account.5.dtmf.in_RFC2833 = 1
account.5.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))
account.5.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))
account.5.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)
account.5.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))
account.5.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)
account.5.media_type_change = 0

#Configure the MSN_DDI of account
account.5.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)
account.5.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))
account.5.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).
#Presented prefix 1 ("00" - Default)
account.5.intl_clip.presented.1 = 00

#Incoming prefix 2.
account.5.intl_clip.incoming.2 =

#Presented prefix 2.
account.5.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)
account.5.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

provision-platan-gateway-GW24

Line6 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.6.enable = 0

#Configure the ID
account.6.id =

#Configure the SIP server address (domain) and port
account.6.sip_server_host =

#Configure the register user name
account.6.user_name =

#Configure the register password
account.6.password =

#Configure Dial number (#000 to #999)
account.6.extension_number = #206

#Configure the display name of account
account.6.display_name =

#Configure the SIP server proxy
account.6.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.6.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.6.call_recording_announcement = 0

Advanced settings

#Domain
account.6.domain =

#Configure the sip server expires (Timeout 60 by default)
account.6.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.6.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

provision-platan-gateway-GW24

account.6.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.6.dtmf.out_RFC2833 = 1

account.6.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.6.dtmf.in_DTMF = 1

account.6.dtmf.in_RFC2833 = 1

account.6.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.6.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.6.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.6.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.6.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.6.media_type_change = 0

#Configure the MSN_DDI of account

account.6.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.6.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.6.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.6.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.6.intl_clip.incoming.2 =

#Presented prefix 2.

account.6.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.6.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

provision-platan-gateway-GW24

Line7 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.7.enable = 0

#Configure the ID
account.7.id =

#Configure the SIP server address (domain) and port
account.7.sip_server_host =

#Configure the register user name
account.7.user_name =

#Configure the register password
account.7.password =

#Configure Dial number (#000 to #999)
account.7.extension_number = #207

#Configure the display name of account
account.7.display_name =

#Configure the SIP server proxy
account.7.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.7.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.7.call_recording_announcement = 0

Advanced settings

#Domain
account.7.domain =

#Configure the sip server expires (Timeout 60 by default)
account.7.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.7.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.7.number.type = 0

provision-platan-gateway-GW24

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.7.dtmf.out_RFC2833 = 1

account.7.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.7.dtmf.in_DTMF = 1

account.7.dtmf.in_RFC2833 = 1

account.7.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.7.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.7.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.7.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.7.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.7.media_type_change = 0

#Configure the MSN_DDI of account

account.7.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.7.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.7.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.7.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.7.intl_clip.incoming.2 =

#Presented prefix 2.

account.7.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.7.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

provision-platan-gateway-GW24

Line8 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.8.enable = 0

#Configure the ID
account.8.id =

#Configure the SIP server address (domain) and port
account.8.sip_server_host =

#Configure the register user name
account.8.user_name =

#Configure the register password
account.8.password =

#Configure Dial number (#000 to #999)
account.8.extension_number = #208

#Configure the display name of account
account.8.display_name =

#Configure the SIP server proxy
account.8.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.8.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.8.call_recording_announcement = 0

Advanced settings

#Domain
account.8.domain =

#Configure the sip server expires (Timeout 60 by default)
account.8.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.8.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.8.number.type = 0

provision-platan-gateway-GW24

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.8.dtmf.out_RFC2833 = 1

account.8.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.8.dtmf.in_DTMF = 1

account.8.dtmf.in_RFC2833 = 1

account.8.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.8.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.8.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.8.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.8.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.8.media_type_change = 0

#Configure the MSN_DDI of account

account.8.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.8.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.8.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.8.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.8.intl_clip.incoming.2 =

#Presented prefix 2.

account.8.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.8.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line9 settings

provision-platan-gateway-GW24

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.9.enable = 0

#Configure the ID
account.9.id =

#Configure the SIP server address (domain) and port
account.9.sip_server_host =

#Configure the register user name
account.9.user_name =

#Configure the register password
account.9.password =

#Configure Dial number (#000 to #999)
account.9.extension_number = #209

#Configure the display name of account
account.9.display_name =

#Configure the SIP server proxy
account.9.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.9.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.9.call_recording_announcement = 0

Advanced settings

#Domain
account.9.domain =

#Configure the sip server expires (Timeout 60 by default)
account.9.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.9.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.9.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

provision-platan-gateway-GW24

account.9.dtmf.out_RFC2833 = 1
account.9.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.9.dtmf.in_DTMF = 1
account.9.dtmf.in_RFC2833 = 1
account.9.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.9.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.9.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.9.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.9.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.9.media_type_change = 0

#Configure the MSN_DDI of account

account.9.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.9.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.9.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.9.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.9.intl_clip.incoming.2 =

#Presented prefix 2.

account.9.intl_clip.presented.2 =

#Dialplan rule (112|9|[89]x|11|[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.9.dialplan_rule = (112|9|[89]x|11|[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line10 settings

#####

provision-platan-gateway-GW24

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.10.enable = 0

#Configure the ID
account.10.id =

#Configure the SIP server address (domain) and port
account.10.sip_server_host =

#Configure the register user name
account.10.user_name =

#Configure the register password
account.10.password =

#Configure Dial number (#000 to #999)
account.10.extension_number = #210

#Configure the display name of account
account.10.display_name =

#Configure the SIP server proxy
account.10.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.10.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.10.call_recording_announcement = 0

Advanced settings

#Domain
account.10.domain =

#Configure the sip server expires (Timeout 60 by default)
account.10.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.10.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.10.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled
account.10.dtmf.out_RFC2833 = 1

provision-platan-gateway-GW24

account.10.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.10.dtmf.in_DTMF = 1

account.10.dtmf.in_RFC2833 = 1

account.10.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.10.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.10.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.10.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.10.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.10.media_type_change = 0

#Configure the MSN_DDI of account

account.10.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.10.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.10.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.10.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.10.intl_clip.incoming.2 =

#Presented prefix 2.

account.10.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.10.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line11 settings

#####

provision-platan-gateway-GW24

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.11.enable = 0

#Configure the ID
account.11.id =

#Configure the SIP server address (domain) and port
account.11.sip_server_host =

#Configure the register user name
account.11.user_name =

#Configure the register password
account.11.password =

#Configure Dial number (#000 to #999)
account.11.extension_number = #211

#Configure the display name of account
account.11.display_name =

#Configure the SIP server proxy
account.11.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.11.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.11.call_recording_announcement = 0

Advanced settings

#Domain
account.11.domain =

#Configure the sip server expires (Timeout 60 by default)
account.11.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.11.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.11.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled
account.11.dtmf.out_RFC2833 = 1
account.11.dtmf.out_SIP_INFO = 1

provision-platan-gateway-GW24

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.11.dtmf.in_DTMF = 1
account.11.dtmf.in_RFC2833 = 1
account.11.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.11.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.11.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.11.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.11.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.11.media_type_change = 0

#Configure the MSN_DDI of account

account.11.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.11.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.11.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.11.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.11.intl_clip.incoming.2 =

#Presented prefix 2.

account.11.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.11.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line12 settings

#####

Basic settings

provision-platan-gateway-GW24

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.12.enable = 0

#Configure the ID
account.12.id =

#Configure the SIP server address (domain) and port
account.12.sip_server_host =

#Configure the register user name
account.12.user_name =

#Configure the register password
account.12.password =

#Configure Dial number (#000 to #999)
account.12.extension_number = #212

#Configure the display name of account
account.12.display_name =

#Configure the SIP server proxy
account.12.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.12.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.12.call_recording_announcement = 0

Advanced settings

#Domain
account.12.domain =

#Configure the sip server expires (Timeout 60 by default)
account.12.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.12.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.12.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled
account.12.dtmf.out_RFC2833 = 1
account.12.dtmf.out_SIP_INFO = 1

provision-platan-gateway-GW24

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.12.dtmf.in_DTMF = 1
account.12.dtmf.in_RFC2833 = 1
account.12.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.12.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.12.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.12.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.12.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.12.media_type_change = 0

#Configure the MSN_DDI of account

account.12.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.12.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.12.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.12.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.12.intl_clip.incoming.2 =

#Presented prefix 2.

account.12.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.12.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line13 settings

#####

Basic settings

provision-platan-gateway-GW24

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.13.enable = 0

#Configure the ID
account.13.id =

#Configure the SIP server address (domain) and port
account.13.sip_server_host =

#Configure the register user name
account.13.user_name =

#Configure the register password
account.13.password =

#Configure Dial number (#000 to #999)
account.13.extension_number = #213

#Configure the display name of account
account.13.display_name =

#Configure the SIP server proxy
account.13.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.13.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.13.call_recording_announcement = 0

Advanced settings

#Domain
account.13.domain =

#Configure the sip server expires (Timeout 60 by default)
account.13.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.13.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.13.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled
account.13.dtmf.out_RFC2833 = 1
account.13.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

provision-platan-gateway-GW24

account.13.dtmf.in_DTMF = 1
account.13.dtmf.in_RFC2833 = 1
account.13.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))
account.13.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))
account.13.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)
account.13.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))
account.13.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)
account.13.media_type_change = 0

#Configure the MSN_DDI of account
account.13.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)
account.13.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))
account.13.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).
#Presented prefix 1 ("00" - Default)
account.13.intl_clip.presented.1 = 00

#Incoming prefix 2.
account.13.intl_clip.incoming.2 =

#Presented prefix 2.
account.13.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)
account.13.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line14 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled

provision-platan-gateway-GW24

account.14.enable = 0

#Configure the ID

account.14.id =

#Configure the SIP server address (domain) and port

account.14.sip_server_host =

#Configure the register user name

account.14.user_name =

#Configure the register password

account.14.password =

#Configure Dial number (#000 to #999)

account.14.extension_number = #214

#Configure the display name of account

account.14.display_name =

#Configure the SIP server proxy

account.14.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)

account.14.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)

account.14.call_recording_announcement = 0

Advanced settings

#Domain

account.14.domain =

#Configure the sip server expires (Timeout 60 by default)

account.14.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

account.14.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.14.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.14.dtmf.out_RFC2833 = 1

account.14.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.14.dtmf.in_DTMF = 1

provision-platan-gateway-GW24

account.14.dtmf.in_RFC2833 = 1
account.14.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))
account.14.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))
account.14.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)
account.14.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))
account.14.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)
account.14.media_type_change = 0

#Configure the MSN_DDI of account
account.14.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)
account.14.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))
account.14.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).
#Presented prefix 1 ("00" - Default)
account.14.intl_clip.presented.1 = 00

#Incoming prefix 2.
account.14.intl_clip.incoming.2 =

#Presented prefix 2.
account.14.intl_clip.presented.2 =

#Dialplan rule (112)9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)
account.14.dialplan_rule = (112)9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line15 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.15.enable = 0

provision-platan-gateway-GW24

#Configure the ID

account.15.id =

#Configure the SIP server address (domain) and port

account.15.sip_server_host =

#Configure the register user name

account.15.user_name =

#Configure the register password

account.15.password =

#Configure Dial number (#000 to #999)

account.15.extension_number = #215

#Configure the display name of account

account.15.display_name =

#Configure the SIP server proxy

account.15.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)

account.15.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)

account.15.call_recording_announcement = 0

Advanced settings

#Domain

account.15.domain =

#Configure the sip server expires (Timeout 60 by default)

account.15.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

account.15.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.15.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.15.dtmf.out_RFC2833 = 1

account.15.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.15.dtmf.in_DTMF = 1

account.15.dtmf.in_RFC2833 = 1

provision-platan-gateway-GW24

```
account.15.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))
account.15.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))
account.15.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)
account.15.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))
account.15.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)
account.15.media_type_change = 0

#Configure the MSN_DDI of account
account.15.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)
account.15.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))
account.15.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).
#Presented prefix 1 ("00" - Default)
account.15.intl_clip.presented.1 = 00

#Incoming prefix 2.
account.15.intl_clip.incoming.2 =

#Presented prefix 2.
account.15.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)
account.15.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

##### Line16 settings
#####

##### Basic settings #####

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.16.enable = 0
```


provision-platan-gateway-GW24

#Configure the ID

account.16.id =

#Configure the SIP server address (domain) and port

account.16.sip_server_host =

#Configure the register user name

account.16.user_name =

#Configure the register password

account.16.password =

#Configure Dial number (#000 to #999)

account.16.extension_number = #216

#Configure the display name of account

account.16.display_name =

#Configure the SIP server proxy

account.16.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)

account.16.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)

account.16.call_recording_announcement = 0

Advanced settings

#Domain

account.16.domain =

#Configure the sip server expires (Timeout 60 by default)

account.16.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

account.16.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.16.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.16.dtmf.out_RFC2833 = 1

account.16.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.16.dtmf.in_DTMF = 1

account.16.dtmf.in_RFC2833 = 1

account.16.dtmf.in_SIP_INFO = 1

provision-platan-gateway-GW24

```
#NAT keep alive (0-Disabled, 1-Enabled (default))
account.16.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))
account.16.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)
account.16.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))
account.16.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)
account.16.media_type_change = 0

#Configure the MSN_DDI of account
account.16.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)
account.16.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))
account.16.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).
#Presented prefix 1 ("00" - Default)
account.16.intl_clip.presented.1 = 00

#Incoming prefix 2.
account.16.intl_clip.incoming.2 =

#Presented prefix 2.
account.16.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)
account.16.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

##### Line17 settings
#####

##### Basic settings #####

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled
account.17.enable = 0

#Configure the ID
```

provision-platan-gateway-GW24

account.17.id =

#Configure the SIP server address (domain) and port

account.17.sip_server_host =

#Configure the register user name

account.17.user_name =

#Configure the register password

account.17.password =

#Configure Dial number (#000 to #999)

account.17.extension_number = #217

#Configure the display name of account

account.17.display_name =

#Configure the SIP server proxy

account.17.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)

account.17.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)

account.17.call_recording_announcement = 0

Advanced settings

#Domain

account.17.domain =

#Configure the sip server expires (Timeout 60 by default)

account.17.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

account.17.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.17.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.17.dtmf.out_RFC2833 = 1

account.17.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.17.dtmf.in_DTMF = 1

account.17.dtmf.in_RFC2833 = 1

account.17.dtmf.in_SIP_INFO = 1

provision-platan-gateway-GW24

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.17.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.17.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.17.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.17.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.17.media_type_change = 0

#Configure the MSN_DDI of account

account.17.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.17.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.17.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.17.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.17.intl_clip.incoming.2 =

#Presented prefix 2.

account.17.intl_clip.presented.2 =

#Dialplan rule ((112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.17.dialplan_rule = ((112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line18 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled

account.18.enable = 0

#Configure the ID

account.18.id =

provision-platan-gateway-GW24

#Configure the SIP server address (domain) and port

account.18.sip_server_host =

#Configure the register user name

account.18.user_name =

#Configure the register password

account.18.password =

#Configure Dial number (#000 to #999)

account.18.extension_number = #218

#Configure the display name of account

account.18.display_name =

#Configure the SIP server proxy

account.18.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)

account.18.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)

account.18.call_recording_announcement = 0

Advanced settings

#Domain

account.18.domain =

#Configure the sip server expires (Timeout 60 by default)

account.18.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

account.18.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.18.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.18.dtmf.out_RFC2833 = 1

account.18.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.18.dtmf.in_DTMF = 1

account.18.dtmf.in_RFC2833 = 1

account.18.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

provision-platan-gateway-GW24

account.18.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.18.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.18.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.18.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.18.media_type_change = 0

#Configure the MSN_DDI of account

account.18.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.18.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.18.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.18.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.18.intl_clip.incoming.2 =

#Presented prefix 2.

account.18.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.18.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line19 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled

account.19.enable = 0

#Configure the ID

account.19.id =

provision-platan-gateway-GW24

#Configure the SIP server address (domain) and port
account.19.sip_server_host =

#Configure the register user name
account.19.user_name =

#Configure the register password
account.19.password =

#Configure Dial number (#000 to #999)
account.19.extension_number = #219

#Configure the display name of account
account.19.display_name =

#Configure the SIP server proxy
account.19.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.19.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.19.call_recording_announcement = 0

Advanced settings

#Domain
account.19.domain =

#Configure the sip server expires (Timeout 60 by default)
account.19.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.19.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.19.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled
account.19.dtmf.out_RFC2833 = 1
account.19.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)
account.19.dtmf.in_DTMF = 1
account.19.dtmf.in_RFC2833 = 1
account.19.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))
account.19.nat_udp_update_enable = 1

provision-platan-gateway-GW24

#Send number after # (0-Disabled, 1-Enabled (default))

account.19.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.19.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.19.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.19.media_type_change = 0

#Configure the MSN_DDI of account

account.19.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.19.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.19.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.19.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.19.intl_clip.incoming.2 =

#Presented prefix 2.

account.19.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.19.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line20 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled

account.20.enable = 0

#Configure the ID

account.20.id =

#Configure the SIP server address (domain) and port

provision-platan-gateway-GW24

account.20.sip_server_host =

#Configure the register user name

account.20.user_name =

#Configure the register password

account.20.password =

#Configure Dial number (#000 to #999)

account.20.extension_number = #220

#Configure the display name of account

account.20.display_name =

#Configure the SIP server proxy

account.20.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)

account.20.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)

account.20.call_recording_announcement = 0

Advanced settings

#Domain

account.20.domain =

#Configure the sip server expires (Timeout 60 by default)

account.20.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

account.20.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.20.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.20.dtmf.out_RFC2833 = 1

account.20.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.20.dtmf.in_DTMF = 1

account.20.dtmf.in_RFC2833 = 1

account.20.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.20.nat.udp_update_enable = 1

provision-platan-gateway-GW24

#Send number after # (0-Disabled, 1-Enabled (default))

account.20.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.20.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.20.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.20.media_type_change = 0

#Configure the MSN_DDI of account

account.20.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.20.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.20.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.20.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.20.intl_clip.incoming.2 =

#Presented prefix 2.

account.20.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.20.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line21 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled

account.21.enable = 0

#Configure the ID

account.21.id =

#Configure the SIP server address (domain) and port

account.21.sip_server_host =

provision-platan-gateway-GW24

#Configure the register user name

account.21.user_name =

#Configure the register password

account.21.password =

#Configure Dial number (#000 to #999)

account.21.extension_number = #221

#Configure the display name of account

account.21.display_name =

#Configure the SIP server proxy

account.21.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)

account.21.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)

account.21.call_recording_announcement = 0

Advanced settings

#Domain

account.21.domain =

#Configure the sip server expires (Timeout 60 by default)

account.21.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

account.21.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.21.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.21.dtmf.out_RFC2833 = 1

account.21.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.21.dtmf.in_DTMF = 1

account.21.dtmf.in_RFC2833 = 1

account.21.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.21.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

provision-platan-gateway-GW24

account.21.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.21.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.21.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.21.media_type_change = 0

#Configure the MSN_DDI of account

account.21.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.21.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.21.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.21.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.21.intl_clip.incoming.2 =

#Presented prefix 2.

account.21.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.21.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line22 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled

account.22.enable = 0

#Configure the ID

account.22.id =

#Configure the SIP server address (domain) and port

account.22.sip_server_host =

provision-platan-gateway-GW24

#Configure the register user name
account.22.user_name =

#Configure the register password
account.22.password =

#Configure Dial number (#000 to #999)
account.22.extension_number = #222

#Configure the display name of account
account.22.display_name =

#Configure the SIP server proxy
account.22.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)
account.22.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)
account.22.call_recording_announcement = 0

Advanced settings

#Domain
account.22.domain =

#Configure the sip server expires (Timeout 60 by default)
account.22.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name
account.22.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID
account.22.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled
account.22.dtmf.out_RFC2833 = 1
account.22.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)
account.22.dtmf.in_DTMF = 1
account.22.dtmf.in_RFC2833 = 1
account.22.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))
account.22.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))
account.22.send_after_hash = 1

provision-platan-gateway-GW24

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.22.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.22.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.22.media_type_change = 0

#Configure the MSN_DDI of account

account.22.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.22.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.22.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.22.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.22.intl_clip.incoming.2 =

#Presented prefix 2.

account.22.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.22.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line23 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled

account.23.enable = 0

#Configure the ID

account.23.id =

#Configure the SIP server address (domain) and port

account.23.sip_server_host =

#Configure the register user name

provision-platan-gateway-GW24

account.23.user_name =

#Configure the register password

account.23.password =

#Configure Dial number (#000 to #999)

account.23.extension_number = #223

#Configure the display name of account

account.23.display_name =

#Configure the SIP server proxy

account.23.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)

account.23.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)

account.23.call_recording_announcement = 0

Advanced settings

#Domain

account.23.domain =

#Configure the sip server expires (Timeout 60 by default)

account.23.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

account.23.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.23.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.23.dtmf.out_RFC2833 = 1

account.23.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.23.dtmf.in_DTMF = 1

account.23.dtmf.in_RFC2833 = 1

account.23.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.23.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.23.send_after_hash = 1

provision-platan-gateway-GW24

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

account.23.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.23.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.23.media_type_change = 0

#Configure the MSN_DDI of account

account.23.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.23.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.23.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.23.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.23.intl_clip.incoming.2 =

#Presented prefix 2.

account.23.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.23.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)

Line24 settings

#####

Basic settings

#Activate/Deactivate the account, 0-Disabled (Default), 1-Enabled

account.24.enable = 0

#Configure the ID

account.24.id =

#Configure the SIP server address (domain) and port

account.24.sip_server_host =

#Configure the register user name

account.24.user_name =

provision-platan-gateway-GW24

#Configure the register password

account.24.password =

#Configure Dial number (#000 to #999)

account.24.extension_number = #224

#Configure the display name of account

account.24.display_name =

#Configure the SIP server proxy

account.24.outbound_proxy_enable =

#Call recording (0-Disabled (Default), 1-Enabled)

account.24.call_recording_enable = 0

#Announcement (0-None (Default), 1 to 4)

account.24.call_recording_announcement = 0

Advanced settings

#Domain

account.24.domain =

#Configure the sip server expires (Timeout 60 by default)

account.24.sip_server_expires = 60

#Źródło CLIP, 0-User name (Default), 1-Display name

account.24.source_clip = 0

#Typ numeru MSN, 0-From (Default), 1-Remote-Party-ID

account.24.number.type = 0

#Wybór sposobu transmisji sygnalizacji nadawanej DTMF, (DTMF Default), 0-Disabled, 1-Enabled

account.24.dtmf.out_RFC2833 = 1

account.24.dtmf.out_SIP_INFO = 1

#Wybór sposobu transmisji sygnalizacji odbieranej DTMF (0-Disabled, 1-Enabled)

account.24.dtmf.in_DTMF = 1

account.24.dtmf.in_RFC2833 = 1

account.24.dtmf.in_SIP_INFO = 1

#NAT keep alive (0-Disabled, 1-Enabled (default))

account.24.nat.udp_update_enable = 1

#Send number after # (0-Disabled, 1-Enabled (default))

account.24.send_after_hash = 1

#T.38 Fax Relay (0-Disabled (default), 1-Enabled)

provision-platan-gateway-GW24

account.24.T38.relay_enable = 0

#Require T.38 standard for incoming fax (0-Disabled, 1-Enabled (default))

account.24.T38.require_in_enable = 0

#Allow media type change (0-Disabled (default), 1-Enabled)

account.24.media_type_change = 0

#Configure the MSN_DDI of account

account.24.msn_ddi =

#CLIR (hide own number) (0-Disabled (default), 1-Enabled)

account.24.clir_enable = 0

#International CLIP detection (0-Disabled, 1-Enabled (Default))

account.24.intl_clip.detection = 1

#Incoming prefix 1 : "+" (Default).

#Presented prefix 1 ("00" - Default)

account.24.intl_clip.presented.1 = 00

#Incoming prefix 2.

account.24.intl_clip.incoming.2 =

#Presented prefix 2.

account.24.intl_clip.presented.2 =

#Dialplan rule (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3) (default)

account.24.dialplan_rule = (112|9[89]x|11[68]xxx|19xxx|[1-9]xxxxxxxx|00x.S3|x.S3)